

The image displays four different models of fiber optic couplers, each in a separate white-bordered box. From left to right: 1. CW4-★A-S(002): A small, square, silver-colored metal component with two green fiber ports on opposite sides. 2. CW4L2-★A-S(002): A rectangular, silver-colored metal component with two green fiber ports on one side and a black connector on the other. 3. CW4L3-★A-S(002): A larger, rectangular, silver-colored metal component with two green fiber ports on one side and a black connector on the other. 4. YS83Q2DN-★A: A small, rectangular, silver-colored metal component with two green fiber ports on one side and a black connector on the other.

- 直流电源滤波器
DC filters
 - 多种极数可供选择
Multiple pole to choose from
 - 欧式端子连接安全快捷
European style terminal block connected is safe and quick
 - 多种安装方式可供选择
Multiple installation methods to choose from

- CW4→ A-S(002) 螺丝固定单极滤波器
Unipolar filter by screw fixed
- CW4L2-→A-S(002) 螺丝固定双极滤波器
Bipolar filter by screw fixed
- CW4L3-→A-S(002) 螺丝固定三极滤波器
Three pole filter by screw fixed
- YS83Q2DN-→A 底部导轨固定双极滤波器
Bipolar filter by bottom guide rail fixed

APPLICATION

- | | | |
|--|-------------------------------|--------------------------------------|
| 电子电气设备
ElectricalandElectronicEquipment | 医疗设备
MedicalEquipment | 办公自动化设备
OfficeAutomationEquipment |
| 消费电子
ConsumerElectronicProduction | 数据通讯设备
DataCommunication | 开关电源
Switchingpowersupply |
| 程控交换机
SPCexchange | 监控设备
Surveillanceequipment | 各类直流电子设备
DC electronic equipment |

TECHNICAL DATA

- | | | | |
|-------------------------|--------------|-----------------------------|----------------------|
| ■ 额定电压/ Rated Voltage : | 12/24/48V DC | ■ 气候类型/ Climatic Category : | 25/85/21 |
| ■ 额定电流/ Rated Current : | 1-30A | ■ 测试电压/ Working Frequency : | 50V DC(Line to Line) |

产品型号 PartNo.	额定电流(A) RateCurrent	电路图 Schematics	外形尺寸 Dimension	出线方式 Connection	安装方式 Installation	重量(g) Weigh	安规认证 Certification
CW4-•A-S(002)	1/3/6/10/20/30	B17	A33		螺丝 Screw	203	CE RoHS
CW4L2-•A-S(002)	1/3/6/10/20/30	B21	A39		螺丝 Screw	363	CE RoHS
CW4L3-•A-S(002)	1/3/6/10/20/30	B23	A42		螺丝 Screw	563	CE RoHS
YS83Q2DN-•A	1/3/6/10/20/30	B26	A47		导轨 Rail	363	CE RoHS

A33

Top view dimensions: 89±1, 77±0.5, 65±2, 35±0.5, 21, 4.4, 60±1, 4×ø4.0, 20, 39±0.5.

Side view dimensions: 56±2, 45±1, 4.4, 6.

A39

Top view dimensions: 94±2, 87±1, 72±1, 56±2, 45±1, 4.4, 6.

Side view dimensions: 39.5.

A42

Top view dimensions: 144±1, 133±1, 120±1, 45±1, 4.4, 6, 44±0.5, 58±2, 4×ø4.0.

Side view dimensions: 56±2, 48.5±1, 45±1, 4.4, 6.

A47

Top view dimensions: 94±2, 72±1, 56±2, 45±1, 48.5±1, 4.4, 6.

Side view dimensions: 39.5.

SCHEMATICS

